

## TECHNICAL SPECIFICATIONS

### Cetra®536 Whirlpool Bath

CET6036 WLR 2XX Cetra 536 Whirlpool Bath Left Hand (N875)  
 CET6036 WRL 2XX Cetra 536 Whirlpool Bath Right Hand (N880)

### Cetra® 536 Bath

CET6036 BUX XXX Cetra 536 Bath (N885)



#### INSTALLATION NOTES

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

## KEY DIMENSIONS

#### DIMENSIONS

60" L x 36" W x 21-1/4" H  
 (1524 mm) L x (914 mm) W x (540 mm) H

#### DRAIN/OVERFLOW

A: 18-1/2" (470 mm) B: 9" (229 mm)

#### CUTOUT

58" x 34-1/4"

#### TOTAL WEIGHT

N875, N880: 742 lb (337 kg) / 50 lb/sq. ft. (242 kg/m<sup>2</sup>)

N885: 707 lb (321 kg) / 47 lb/sq. ft. (230 kg/m<sup>2</sup>)

#### OPERATING GALLONAGE

48 U.S. Gal. (181 Liters)

Max. 55 U.S. Gal. (208 Liters)

#### PRODUCT WEIGHT

N875, N880: 92 lb (42 kg)

N885: 57 lb (26 kg)

#### SKIRT MOUNTING

Optional U-Frame

#### ELECTRICAL SPECIFICATIONS MODELS N875, N880 ONLY

Requires a dedicated GFCI protected separate circuit.

Motor/Pump: 120 VAC, 15 AMP, 60 Hz.

RapidHeat™: 120 VAC, 15 AMP, 60 Hz.

#### HEATER (OPTIONAL) MODELS N875, N880 ONLY

Requires a dedicated GFCI protected separate circuit.

RapidHeat™: P/N S750000

Product Shown: Cetra 536 Whirlpool Bath Left Hand Model: N875

\* Measurements inside unit represent cutout in floor to allow for drain/overflow. Minimum Service Access dimensions given.

## FEATURES, UPGRADES & ACCESSORIES

- Right and Left Hand Drain Location
- Accessories / Hardware:
  - Trip-Lever Drain Kit: #X559
  - Rotary Drain Kit, 26" Cable: #8730
  - Trim Kit: 1 X TheraPro™ Jet Rings #D095
  - Trim Kit: 2 X AccuPro™ Jet Rings #J869
- Trim Kit Finishes Available:
  - (827) – Chrome
  - (826) – Brushed Nickel
  - (849) – Oil Rubbed Bronze

