

Bravo™ Technical Specifications

Soaking Bath Model		
Letter	Description	
-	Drain/Motor Location	Center Drain
-	Cutout	N/A
-	Total Weight	922 lbs (418 kg)
-	Floor Loading	55.8 lb/ft ² (272.4 kg/m ²)
-	Operating Gallons (Min/Max)	48 Gal. (182 L) Min. 60 Gal. (227 L) Max.
-	Product Weight	122 lbs (55 kg)
-	Soaking Depth	16" (406 mm)
L	Outer Length	65-1/2" (1664 mm)
W	Outer Width	35-5/8" (905 mm)
H	Overall Height	24" (610 mm)
A	Overflow Height	20" (508 mm)
B	Short Edge to Drain Center	32-3/4" (832 mm)
C	Long Edge to Drain Center	17-3/4" (451 mm)
D	Drain Shoe Length	12-3/4" (324 mm)
E	Flange Height	N/A
F	Deck Width	5" (127 mm)
G	Service Access Dimensions	N/A
I	Floor Cutout for Drain	6 x 18" (150 x 457 mm)
J	Interior Dimensions (W x L)	46" x 20-1/4" (1168 mm x 514 mm)
K	Skirt Base Dimensions: K(L) x K(W)	50" x 30" (1270 mm x 762 mm)
M	Backrest Angle	18°

Pure Air® Bath Model		
Letter	Description	
-	Drain/Motor Location	Center Drain
-	Cutout	N/A
-	Total Weight	931 lbs (427 kg)
-	Floor Loading	56.4 lb/ft ² (275.3 kg/m ²)
-	Operating Gallons (Min/Max)	48 Gal. (182 L) Min. 60 Gal. (227 L) Max.
-	Product Weight	131 lbs (59 kg)
-	Soaking Depth	16" (406 mm)
L	Outer Length	65-1/2" (1664 mm)
W	Outer Width	35-5/8" (905 mm)
H	Overall Height	24" (610 mm)
A	Overflow Height	20" (508 mm)
B	Short Edge to Drain Center	32-3/4" (832 mm)
C	Long Edge to Drain Center	17-3/4" (451 mm)
D	Drain Shoe Length	12-3/4" (324 mm)
E	Flange Height	N/A
F	Deck Width	5" (127 mm)
G	Service Access Dimensions	N/A
I	Floor Cutout for Drain	6 x 18" (150 x 457 mm)
J	Interior Dimensions (W x L)	46" x 20-1/4" (1168 mm x 514 mm)
K	Skirt Base Dimensions: K(L) x K(W)	50" x 30" (1270 mm x 762 mm)
M	Backrest Angle	18°

Key Dimensions

